FFATURES

STANDARD



OPTIONAL





USED BY:

- BANKS/CREDIT INSTITUTIONS
- INSURANCE COMPANIES
- PRIVATE ORGANIZATIONS
- RETAIL STORES
- HOTELS
- AMUSEMENT PARKS
- FAST FOOD
- PUBLIC ADMINISTRATION
- HOSPITALS
- TRANSPORT COMPANIES
- CLUBS/ASSOCIATIONS
- SERVICE BUREAUS

IDEAL FOR:

- CREDIT CARDS AND OTHER FINANCIAL CARDS*
- ID CARDS
- GIFT CARDS
- PREPAID CARDS
- ACCESS CONTROL
- FIDELITY CARDS
- PATIENT ID CARDS
- DISCOUNT CARDS
- * Compatible with most 3rd party EMV personalization software solutions

SOFTWARE

INSTANT CARD



MAXIMA SERIES 821-821T-861



UNSURPASSED RELIABILITY

FOR YOUR CARD PERSONALIZATION REQUIREMENTS

- ✓ 60/80/105 characters capacity drum
- ✓ One pass to emboss and front or rear infill (optional)
- ✓ Encoding:

Magnetic stripe (ISO)
Smart Card Contact Station





Embossing and infill





Internal tipping unit

MAXIMA 821 MAXIMA 821T

INSTANTCARD



certification for MAXIMA 861 only





TECHNICAL FEATURES

CARD & FEEDER

card specifications CR80 - CR50 - ISO standard

card materials Abs, pvc and composite - thickness: 0,5 ÷ 0,8 mm / 20 ÷ 32 mil

input hopper 821/821T: manual feed - Single Access Point

861: 200 cards capacity automatic hopper - FIFO (First In - First Out)

output hopper 861: 100 embossed cards
reject hopper 861: 10 cards capacity
821/821T: alarm notification

EMBOSSING

technology embossing & ident

drum capacity 60/80/105 characters standard; 120 characters drum for MAXIMA 821T on request

characters Standard Gothic, OCR7B, country specific characters (optional), etc.

embossing area 12 lines x 31 characters (76 x 52 mm area / 3" x 2.05" in)

internal tipping unit 821T/861: off line tipping option (76 x 41 mm area / 3" x 1.61" in). Ribbon saving function

infill unit optional infill (available fonts OCRB1/B4 and others) or rear infill device (CW2 - OCRA1)

performance* 821: 240 CHP (1 card in 15 seconds)

861: 260 CHP (1 card in 13.8 seconds)

*depending on the job

ENCODING OPTIONS

magnetic encoding optional: 3 ISO 7811 tracks, LoCo, HiCo

smart card contact

station optional

COMMUNICATION INTERFACE & SOFTWARE

connection interface RS232 serial port

operating systems INSTANT CARD operating with Windows 7/8/10

application program user interface monitoring, card production control, automatic card remake option,

pre-encoded card reading with complete processing operation, system status and

help messages displayed on personal computer

LCD edit optional: offline LCD function

HARDWARE

dimensions (WxDxH) 821: 450 x 485 x 290 mm / 17.7" x 19.1" x 11.4" in

821T: 585 x 485 x 290 mm / 23" x 19.1" x 11.4" in 861: 745 x 485 x 290 mm / 29.3" x 19.1" x 11.4" in

weight 821: 35 kg / 77 lbs

821T: 42 kg / 93 lbs 861: 54 kg / 119 lbs

power supply 100-117-220-230 or 240 Volts - 50 or 60 Hz

operating environment 10° C \div 35° C / 50° F \div 95° F

WARRANTY 12 months

MAXIMA SERIES: CONVENIENT, USER FRIENDLY & VERSATILE, the MAXIMA Series can easily be adapted into a variety of environments and applications. Available with many options such as variable drum capacity, embossing, infill, tipping, magnetic stripe and smart card management, the MAXIMA series meets the requirements of VISA and MasterCard for standard credit card personalization.

The MAXIMA 821T is perfect for decentralized applications that require immediate and small scale card issuance. **The MAXIMA 861** has become a favorite in Banks and Credit Institutions. It's particularly suitable for medium scale card issuance.



Davies Enterprises Ltd. 114 Chain Lake Drive, Halifax, NS B3S1B1 (902) 450-5075



