

The Fastmark® M5e

Shrink Tube Printing



Dynamic defines the compact Fastmark® M5e as it is ideal for printing for shrink tube applications in such markets as transportation or manufacturing for cable harnesses, sleeves, heat shrinkable tubes for wire marking, and others. Thermal transfer high quality prints in 300 dpi means easily readable and durable labels that last for years and withstand temperature extremes, moisture, humidity, abrasion, etc. This is ideal for shrink tube printing.

Traditional Labeling

A second version of the printer is available for 4" wide media thermal printing for barcode labeling (linear and 2D), item/asset and shelf tags, and more... making applications for retail, food preparation, healthcare, logistics, warehouse, shipping, process control, industrial/manufacturing, and government easy.

User Friendly Features

Standard features include an easy to read full color LCD display, max print lengths of 450 inches (300 dpi) to 1,000 inches (203 dpi), and fast printing speed (up to 6 ips for 203 dpi).

It also has 64 MB memory (128 MB flash), adjustable media sensor, and options for WiFi and Bluetooth connectivity. The printer has a low profile so very little space is needed.

It comes equipped with PAL® and emulations for Zebra, Eltron, and Datamax so it handles virtually any data stream easily.

PAL[®]

The AMT Datasouth Difference

For applications with a non-standard emulation or data stream, our proprietary PAL[®] programming language resides in the (smart) Fastmark[®] M5e allowing us to load an app that will accept your data stream and convert (including creating barcodes from the data), format and print to fit your needs. You can unplug whatever your printer is and replace it with the Fastmark[®] M5e printer. And, ongoing service and support, including future changes to the PAL[®] app, if needed, are available for the life of the printer.

Other Features

Printing Method

Direct Thermal and Thermal
Transfer Models Available

Print Speed

203 dpi: 6 ips
300 dpi: 4 ips

Max Print Width

203 dpi: 4.25"
300 dpi: 4.15"

Shrink Tube Print Width

0.15" ~ 2.0"

Sensors

Transmissive Gap
Reflective Black Mark
Printhead Open
Ribbon End
Adjustable Media

Cutter

Optional guillotine



Contact

Get in touch with us today to see if one of our solutions can help you with your printing needs and ultimately, your operational challenges.

AMT Datasouth

www.amtdatasouth.com



Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, California 93012
(805) 388-5799 PH • (805) 484-5282 FX

davies

Davies Enterprises Ltd.
114 Chain Lake Dr., Halifax, NS B3S1B1 (902)450-5075
www.daviesenterprises.com

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH • (704) 525-6104 FX

